

Index

- Aachen model, 19, 247
- Absorption, 2, 10, 22, 44, 60, 61, 63, 68, 71, 72, 74, 77, 109, 216, 260
- Absorption coefficient, 60, 61, 63, 71, 75, 108, 113, 116, 259
- Absorption efficiency, 74, 75, 260
- Active density of states, 50, 57
- Air mass, 22, 23
- Albedo, 36, 37
- Annual degree of efficiency, 15, 246
- Anti-reflection coating, 65, 66, 70, 93, 104, 106
- Area utilization factor, 244
- a-Si, 63, 108–110, 113, 115, 118, 158, 207, 261
- Avalanche breakthrough, 60, 133

- Back-surface-field, 73, 105
- Band diagram, 53, 54, 56, 73, 259
- Bandgap, 48, 49, 60, 63, 71, 77, 81, 83, 87–92, 108–113, 115–117, 119, 181, 218, 269
- Bandgap wavelength, 87, 88
- Band model, 47–49
- Base, 69, 72, 96
- Biomass, 8, 9, 11, 12, 198, 245, 246, 249–251
- Bohr's atomic model, 43
- Bohr's postulate, 43, 44
- Boost converter, 165–167, 171, 172, 175
- Buck converter, 163–165, 167, 196, 262
- Buried contact, 94–96
- Busbar, 69, 70, 94, 219
- Bypass diodes, 136–139, 144, 146, 148, 230, 262

- Cable losses, 152, 229
- Cadmium-telluride (CdTe), 47, 63, 89, 90, 92, 114–117, 123, 125, 126, 129, 130, 144, 146, 153, 173, 207, 261
- CAES, 252
- CdTe, 47, 63, 89, 90, 92, 114–117, 123, 125, 126, 129, 130, 144, 146, 153, 173, 207, 261
- Charge controller, 189, 190, 192, 194–196, 198, 199, 263
- CIGS, 116–118
- CIGSe, 117
- CIS cells, 116, 117, 261
- CISe, 117
- Climate change, 7, 9, 10
- Cloud enhancements, 25
- Compound semiconductor, 47, 115, 116
- Concentrator system, 120, 122, 123, 126, 261
- Conduction band, 48, 49, 53, 54, 56, 60–62, 70, 71, 80, 87
- Conductor, 53, 58
- Conversion efficiency, 177, 179–181
- c-Si, 61, 63, 71, 76, 91, 115, 118, 129, 143, 207, 218, 259, 261, 263
- Current matching, 112
- Czochralski method, 16, 101

- Dangling bonds, 108, 111
- Dark current, 67, 73
- DC/DC converter, 162, 167, 195, 196
- Dead layer, 71, 98, 259
- Degradation, 110–113, 141, 172, 173, 221, 234, 239
- Density of states, effective, 50, 57, 269
- Diffuse radiation, 24, 25

- Diffuse radiation, 123
 Diffusion cell, 110, 261
 Diffusion current, 52, 53, 55, 59, 83, 259
 Diffusion length, 59, 70–72, 97
 Diffusion voltage, 55–58, 60, 259
 Diode characteristics, 59
 Direct radiation, 25
 Direct radiation, 11
 Direct semiconductor, 61–63, 108, 115, 218
 Discontinuous current mode, 165
 Doping, 53–56, 59, 71, 73, 95, 96, 104, 106, 123, 124, 259
 Drift cell, 110, 261
 Drift current, 50
 Drift speed, 50, 51
 Duty cycle, 163, 167, 168
 Dye sensitised solar cell, 120

 EEG, 14, 187, 230–234, 247
 Efficiency, 2, 6, 10, 15–18, 41, 65, 67, 72, 74–76, 80, 87, 90–93, 95–98, 102, 111–122, 129, 141, 146, 171, 175, 177–183, 198, 229, 237, 245, 246, 250, 252, 254, 260, 261
 Efficiency yield, 180
 Efficiency, European, 180, 181, 239, 267
 Efficiency, spectral, 89–91, 260
 Efficiency, theoretical, 90
 EFG, 103, 104, 261
 Electricity, 10
 Electroluminescence measurement, 218
 Electronic grade, 100
 Emitter, 69–72, 74, 77, 95–97, 104, 105, 118, 119
 Emitter, local, 97
 End power, 5
 Energy, 3–9, 11, 244, 245, 250
 Energy bands, 47–49
 Energy payback time, 14
 Equivalent circuit, 69, 77, 78, 83, 85, 87, 141, 187, 260
 ERoEI, 127, 128, 261
 European efficiency, 180, 181, 239, 267
 EVA, 106, 107, 115, 124, 138, 139

 Façade plants, 37
 Feed-in management, 187, 188
 Feed-in variants, 169, 262
 Fermi differences, 57
 Field current, 50–52, 55, 110, 259
 Fill factor, 79, 80, 82–84, 90, 91, 98, 144
 Final yield, 236, 237, 239–242, 264

 Flat roof plants, 155, 227, 241, 242
 Float zone method, 101
 Flyback diode, 165, 167, 181
 Foundation, 153, 154, 156
 Fresnel equations, 93
 Fresnel lens, 120–122
 Full load hours, 27, 29, 30, 200, 202, 236, 239, 258, 265

 GaAs, 18, 47, 63, 89, 90, 92, 119
 Generator connection box, 150, 151, 170
 Generator losses, 236–238
 Generator reference-arrow system, 77, 133, 134
 Global radiation, 24, 123
 Grätzel cell, 120
 Greenhouse effect, 9, 10, 257
 Grid coupling, 2, 14, 18
 Grid operator, 186–188
 Grid parity, 184, 249
 Ground mounted plants, 2

 High efficiency cells, 95
 HIT cell, 106, 118, 119, 129
 Hotspots, 138, 144
 Hybrid wafer cells, 118

 Ideality factor, 77, 83, 85, 87, 262
 Indirect semiconductor, 61–63, 218
 Ingot, 101–103, 124
 Insulator, 48, 49, 106
 Integrated series connection, 114, 115, 221
 Intrinsic carrier concentration, 190, 191
 Inverter, 14, 18, 41, 126, 127, 139, 150, 161, 169–190, 198, 199, 217, 228, 229, 231, 235, 237–242, 263, 267, 268
 Inverter efficiency, 177, 179, 180, 229, 237
 Investment costs, 12, 231
 Irradiance, 21, 22, 24, 35, 60, 61, 64, 74, 78, 79, 88, 91, 121, 141–143, 162, 180, 206, 207, 210, 212, 258, 259, 261, 262
 ITO, 109, 116

 Layered cell, 18, 96, 109, 123
 Learning curve theory, 248
 Learning rate, 248, 249
 Light absorption, 2, 60, 61, 68, 72–74, 109, 216, 259
 Light concentration, 120–122
 Light trapping, 95, 96, 98, 111, 113

- Load reference-arrow system, 68, 77, 140, 147
Local emitter, 97
Local solar time, 31, 32, 225
Low voltage guideline, 186, 188
LST, 31
- Maximum power point, 78, 79
MET, 32
Metallurgical silicon, 99, 100
Methanization, 254
Micro-crystalline, 113, 114
Micromorph, 113, 114
Mismatching, 148, 170, 176, 208, 262
Mobility, 51, 52, 110, 269
Module inverter, 170, 171
Monitoring, 2, 151, 171, 172, 175, 194, 196, 207, 208, 223, 235, 238, 265
Monocrystalline, 81, 93, 101, 102, 106
MOSFET, 164, 171, 172, 176, 189, 195, 196
MPP tracker, 167, 168, 171, 176
Multicrystalline, 102, 103, 126, 127, 159
- NOCT, 143, 146, 262
- Object yield, 35
Off-grid systems, 2, 161, 263
Open air plants, 153
Open circuit voltage, 73, 78–81, 83, 91, 98, 112, 118, 121, 122, 134–136, 141, 142, 146, 183, 188, 194, 262
Operating costs, 231, 232
- Parallel connection, 134, 145
Payback period, 14
Peak power measurement, 213, 213, 263, 268
Peak-shaving, 252, 253
PECVD, 108, 109, 113
Performance Ratio, 237–242, 265
PERL cell, 97, 98, 131
Photocurrent, 219, 260
Photodiode, 68, 207
Photovoltaic, 1–4, 8, 11–19, 21, 25, 30, 33, 38, 39, 101, 123, 124, 130, 133, 150, 158, 161, 176, 181, 188, 199, 232, 233, 238, 246, 251, 267, 275
Pin cell, 109–114
Pitched roof plant, 239–241
Plant monitoring, 208, 235, 265
Plant visualization, 235
- p-n junction, 2, 13, 16, 17, 43, 54–60, 67–69, 73, 83, 91, 92, 95, 104, 105, 109, 117, 133, 218, 259
Point contact cell, 96, 97, 106, 122
Polycrystalline, 101, 102, 116, 117, 123, 153, 158
Polysilicon, 99–102, 124–126
Potential step, 57, 73, 74, 95
Power generation potential, 3, 265
Primary energy, 5–8, 11, 41, 42, 126, 127, 129, 243, 257
Primary energy demand, 126, 127
Primary energy factor, 126
Pyranometer, 205–208, 263
- Quantum efficiency, 75, 76, 98, 113
- Rayleigh scattering, 23
Reactive power, 188, 199
Reactive power provision, 188
Recombination, 49, 70–71, 73, 83, 95, 97, 102, 108–110, 119, 173
Recycling, 123, 124, 128
Reference yield, 235, 236, 237, 239
Reflection factor, 64–66, 93, 95
Refractive index, 66
Renewable energy law (EEG), 14, 19, 187, 230, 231
Ribbon silicon, 103, 104, 130
- Sahara miracle, 2, 41, 42, 243
Saturation current, 85, 87, 91
Shockley equation, 59, 60, 69, 83
Screen printing, 104–106, 219–221
Secondary energy, 5
Self-consumption rate, 169, 184, 185, 234
Self-shading, 226
Semiconductor, 2, 13, 43–66, 73, 83, 87, 95, 100, 115, 116, 119, 120, 126–129
Semiconductor, direct, 61–63, 108, 115
Semiconductor, indirect, 61–63, 218
Sensitivity, spectral, 76, 77, 98, 206, 207, 218
Series connection, 114, 115, 135, 136, 144, 148
Series connection, integrated, 114, 115, 221
Series resistance, 83, 85, 87, 114, 122, 144, 211, 214
Shading analysis, 31–33, 94
Shadow losses, 94
Short circuit current, 78, 79, 81, 85, 112, 121, 146, 147

- Shunt resistance, 83–86, 141, 142, 211
Siemens reactor, 100, 128
Silicon, 13, 15, 18, 45–47, 50, 53, 64, 66, 92, 99–104
Silicon, metallurgical, 99, 100
Simulation software, 27, 36, 184, 225, 228–230
Smart grids, 255
Solar cell, 2, 13, 116, 17, 67–98, 120, 121, 133, 134, 136, 206, 207, 210, 221
Solar cell symbol, 77
Solar constant, 21–23
Solar grade, 100, 128
Solar module, 13–15, 18, 34, 35, 85, 106, 107, 134, 137, 143, 209, 210
Space charge region, 55, 56, 58, 67, 68, 70–72, 109, 110
Specific yield, 15, 232, 241
Spectral efficiency, 87–90, 91
Spectral sensitivity, 76, 77, 98, 206, 207, 218, 219
Staebler-Wronski effect, 110, 111
Standard equivalent circuit, 83, 85, 141
Standard test conditions, 14, 24, 105
STC, 14, 24, 88, 105, 141, 213, 236
Step-down converter, 162
Step-up converter, 165
String, 14, 106, 138, 145, 147, 148, 150, 151, 170, 183, 184, 189, 212, 214, 228, 237
String diode, 145, 147, 150, 151
String fuse, 145
String inverter, 170, 171
String protection, 173
String ribbon, 103
Substrate, 108, 112, 117
Substrate cell, 112
Sun azimuth, 33, 225
Sun declination, 30–32
Sun height, 23, 225
Sun height angle, 23
Sun path diagram, 33, 225
Sun path indicator, 224, 225
Sun position tracking, 24, 225
Superstrate, 109, 112, 116, 173
Superstrate cell, 116
System efficiency, 245
System losses, 236–238
Tandem cell, 112–114, 120
Tce, 6
TCO, 109–114, 118, 173
Tedlar foil, 106
Temperature behavior, 142–143
Temperature coefficient, 81, 82, 115, 129, 133, 142–144
Temperature dependency, 80–82, 115, 118, 207
Texturing, 93, 95, 98
Texturization, 93
Theoretical efficiency, 90–92, 113, 115, 260
Thermal voltage, 59
Thermalization losses, 88, 91
Thermography metrology, 2
Thin film module, 115, 118, 128, 143, 144, 159, 172–175, 220, 221
Thin film cell, 144
Three-component model, 33
Threshold voltage, 60, 136, 139
Toe, 6
Tracking, 38, 40, 154, 167, 168, 175, 181, 195
Transmission losses, 87, 90, 91, 94, 110, 111
Trichlorosilane, 100, 123
Triple cell, 112, 113
Two-diode model, 83, 84
Two-diode, equivalent circuit, 87
UTC, 31
Valence band, 48, 49, 54, 56, 61, 62, 70, 71
VisiKid, 238
Visualization, 238
Wafer, 99, 103–106, 115, 118, 119, 123, 124, 126–128
Wafer cells, hybrid, 118–120
Watt, peak, 14
Weak light behavior, 141, 211, 229
Work, 4, 12, 27, 37, 73, 79, 98, 126, 153, 163, 179, 181, 182, 184, 196, 199, 204, 232, 246
Yield, specific, 15, 232, 235, 236, 241